

Product Information Sheet

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

Supplier's name or trade mark: GLOBOSTAR® GROUP

Supplier's address: GLOBOSTAR® GROUP, THESSALONIKIS 98, 60132 KATERINI KATERINI PIERIAS, EL

Model identifier: SKU: 61019

Type of light source:

| | | | |
|---|------------------------|---------------------------------|------|
| Lighting technology used: | LED | Non-directional or directional: | NDLS |
| Light source cap-type (or other electric interface) | WIRES - TERMINAL BLOCK | | |
| Mains or non-mains: | MLS | Connected light source (CLS): | No |
| Colour-tuneable light source: | Yes | Envelope: | - |
| High luminance light source: | No | | |
| Anti-glare shield: | No | Dimmable: | Yes |

Product parameters


| Parameter | Value | Parameter | Value |
|--|---------------------------|--|------------------------|
| General product parameters: | | | |
| Energy consumption in on-mode (kWh/1000 h), rounded up to the nearest integer | 76 | Energy efficiency class | E |
| Useful luminous flux (ϕ_{use}), indicating if it refers to the flux in a sphere (360°), in a wide cone (120°) or in a narrow cone (90°) | 8 372 in Wide cone (120°) | Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set | 2700...6000 |
| On-mode power (P_{on}), expressed in W | 75,8 | Standby power (P_{sb}), expressed in W and rounded to the second decimal | 0,40 |
| Networked standby power (P_{net}) for CLS, expressed in W and rounded to the second decimal | - | Colour rendering index, rounded to the nearest integer, or the range of CRI-values that can be set | 85 |
| Outer dimensions | Height | Spectral power distribution in the | See image in last page |
| | Width | | |

| | | | | |
|---|-------|------|---------------------------------------|----------------|
| without separate control gear, lighting control parts and non-lighting control parts, if any (millimetre) | Depth | 50 | range 250 nm to 800 nm, at full-load | |
| Claim of equivalent power ^(a) | | Yes | If yes, equivalent power (W) | 200 |
| | | | Chromaticity coordinates (x and y) | 0,370 0,369 |
| Parameters for LED and OLED light sources: | | | | |
| R9 colour rendering index value | | 17 | Survival factor | 0,90 |
| the lumen maintenance factor | | 0,92 | | |
| Parameters for LED and OLED mains light sources: | | | | |
| displacement factor (cos ϕ_1) | | 0,92 | Colour consistency in McAdam ellipses | 5 |
| Claims that an LED light source replaces a fluorescent light source without integrated ballast of a particular wattage. | | -(b) | If yes then replacement claim (W) | - |
| Flicker metric (Pst LM) | | 0,0 | Stroboscopic effect metric (SVM) | 0,0 |

(a)-: not applicable;

(b)-: not applicable;

SDCM: 5.6



x=0.3800 y=0.3800 F4000

