

# CCTV Power Supply

4CH power supply for camera



Two year warranty  
Built-in EMI filter  
100% load test  
Full range of input voltage  
Output voltage accurate and stable  
Output over-voltage, over-current and short-circuit protection  
Output low ripple and noise  
Application:CCTV

## Product Electric Parameters

Input Voltage	AC110-240V
Input Voltage Frequency	60Hz / 50Hz
Output	DC 12V 5A 4CH (60W)
Total Output Current	5A ( 4channels for 4 sets security cameras)
Total Outputs	60W
Fuse Type	GLASS
Fuse Rating 保险丝	1.5Amps / 250VAC

## Protection

General Protection	each output has individual glass (Resetable) fuse and LED indicator, when problem occurs,only affect the individual output, other outputs still working
Circuit Short Protection	when short condition occurs, individual glass (Resetable) fuse will open the circuit,when condition removed, glass (Resetable) fuse will automatically back to close
High Voltage Protection	when high voltage occurs, the surge protection will be hit through to protect the connected device
high temperature protection 最高温度保护	115 degree
Feature	Power ON/OFF switch Unit maintains camera synchronization

Safety standards	Easy installation saves time and eliminates costly labor
E M C standards	According with GB4943, UL60950-1,EN60950-1 standards. According with GB9254, EN55022 class A EN61347-2-13:2008 standards

## Application

CCTV	Camera, PTZ, IR Illuminators, Video Process Equipment, etc
Access Control	Reader, Lock, Panel, etc.
Size (mm)	165(L)*165(M)*45(H)mm
Cooling method	Natural cooling air convection
Weight	Around 0.73KG