

ΕΝΔΙΑΜΕΣΟΙ ΕΞΑΕΡΙΣΤΗΡΕΣ ΑΕΡΑΓΩΓΩΝ

ΣΕΙΡΑ



Διάμετρος	Κωδικός	Ροή αέρα	Θόρυβος	Static pressure	Voltage frequency	Ισχύς	Power consumption	Rev (1/min)	Βαθμός στεγανότητας	Net Βάρος
100	01-152	120/138/198 m3/h	41/46/56 dB (A)	90/100/140 Pa	220-240 V ~50 Hz	18/19/23 W	0,095/0,10/0,11 A	1500/1750/2350	IP X2	1,95 kg
125	01-153	180/200/280 m3/h	41/46/56 dB (A)	90/100/140 Pa	220-240 V ~50 Hz	20/22/25 W	0,098/0,102/0,112 A	1500/1750/2350	IP X2	1,95 kg
150	01-154	288/330/432 m3/h	54/56/63 dB (A)	120/150/220 Pa	220-240 V ~50 Hz	34/36/48 W	0,17/0,18/0,19 A	1450/1700/2250	IP X2	2,75 kg
160	01-155	288/330/432 m3/h	54/56/63 dB (A)	120/150/220 Pa	220-240 V ~50 Hz	34/36/48 W	0,17/0,18/0,19 A	1250/2050/2350	IP X2	2,85 kg
200	01-156	660/750/870 m3/h	61/63/68 dB (A)	240/280/290 Pa	220-240 V ~50 Hz	95/98/105 W	0,44/0,45/0,45 A	1250/2050/2350	IP X2	3,80 kg
250	01-150	1200/1470 m3/h	63/70 dB (A)	165/330 Pa	220-240 V ~50 Hz	134/200 W	0,7/0,9 A	2150/2550	IP X2	7,80 kg
310	01-149	1680/2220 m3/h	63/70 dB (A)	180/360 Pa	220-240 V ~50 Hz	200/290 W	0,9/1,3 A	1650/2150	IP X2	10,5 kg

