

ΕΝΔΙΑΜΕΣΟΙ ΕΞΑΕΡΙΣΤΗΡΕΣ ΑΕΡΑΓΩΓΩΝ

ΣΕΙΡΑ 

Διάμετρος	Κωδικός	Ροή Αέρα	Static Pressure	Θόρυβος	Voltage Frequency	Rev (1/min)	Ισχύς	Max. Operating Temp.	Degree of Protection	Net Weight	Gross Weight
75	01-310	140 m3/h	132 Pa	53 dB	220-230 V ~50 Hz	2820	30 W	-20 ~ +50 °C	IPX2	1,19 kg	1,39 kg
100	01-311	210 m3/h	147 Pa	54 dB	220-230 V ~50 Hz	2770	30 W	-20 ~ +50 °C	IPX2	1,21 kg	1,42 kg
125	01-312	360 m3/h	147 Pa	56 dB	220-230 V ~50 Hz	2615	43 W	-20 ~ +50 °C	IPX2	1,49 kg	1,78 kg
150	01-313	560 m3/h	350 Pa	60 dB	220-230 V ~50 Hz	2530	70 W	-20 ~ +50 °C	IPX2	2 kg	2,39 kg
160	01-314	560 m3/h	350 Pa	60 dB	220-230 V ~50 Hz	2530	70 W	-20 ~ +50 °C	IPX2	2,24 kg	2,60 kg
200	01-315	1400 m3/h	350 Pa	64 dB	220-230 V ~50 Hz	2485	165 W	-20 ~ +50 °C	IPX2	3 kg	3,42 kg
250	01-316	1800 m3/h	460 Pa	72 dB	220-230 V ~50 Hz	2650	180 W	-20 ~ +50 °C	IPX2	5,44 kg	6 kg
310	01-317	2550 m3/h	730 Pa	75 dB	220-230 V ~50 Hz	2510	275 W	-20 ~ +50 °C	IPX2	7,85 kg	8,70 kg


ELECTRONIC STORE

