



Features

- Ultra slim design with 52.5mm(3SU) width
- Universal input 85~264VAC(277VAC operational)
- No load power consumption<0.3W
- Isolation class II
- Pass LPS (Limited power source)
- DC output voltage adjustable
- Protections : Short circuit / Overload / Over voltage
- Cooling by free air convection (working temperature:-30~+70°C)
- DIN rail TS-35/7.5 or 15 mountable
- Over voltage category III
- LED indicator for power on
- 3 years warranty

Applications

- Household control system
- Building automation
- Industrial control system
- Factory automation
- Electro-mechanical apparatus

Description

HDR-60 is one economical ultra slim 60W DIN rail power supply series, adapt to be installed on TS-35/7.5 or TS-35/15 mounting rails. The body is designed 52.5mm(3SU) in width, which allows space saving inside the cabinets. The entire series adopts the full range AC input from 85VAC to 264VAC (277VAC operational) and conforms to EN61000-3-2, the norm the European Union regulates for harmonic current.

HDR-60 is designed with plastic housing that it can effectively prevent user from electric hazards. With working efficiency up to 91%, the entire series can operate at the ambient temperature between -30°C and 70°C under air convection. The complete protection functions and relevant certificates for home automations and industrial control apparatus (IEC60950-1,UL508,UL60950-1,EN61558-2-16) make HDR-60 a very competitive power supply solution for household and industrial applications.

Model Encoding

HDR - 60 - 12

Output voltage

Rated wattage

Series name




60W Ultra Slim Step Shape DIN Rail

HDR-60 series


SPECIFICATION

MODEL		HDR-60-5		HDR-60-12		HDR-60-15		HDR-60-24		HDR-60-48		
OUTPUT	DC VOLTAGE	5V		12V		15V		24V		48V		
	RATED CURRENT	6.5A		4.5A		4A		2.5A		1.25A		
	CURRENT RANGE	0 ~ 6.5A		0 ~ 4.5A		0 ~ 4A		0 ~ 2.5A		0 ~ 1.25A		
	RATED POWER	32.5W		54W		60W		60W		60W		
	RIPPLE & NOISE (max.) Note.2	80mVp-p		120mVp-p		120mVp-p		150mVp-p		240mVp-p		
	VOLTAGE ADJ. RANGE	5.0 ~ 5.5V		10.8 ~ 13.8V		13.5 ~ 18V		21.6 ~ 29V		43.2 ~ 55.2V		
	VOLTAGE TOLERANCE Note.3	± 2.0%		± 1.0%		± 1.0%		± 1.0%		± 1.0%		
	LINE REGULATION	± 1.0%		± 1.0%		± 1.0%		± 1.0%		± 1.0%		
	LOAD REGULATION	± 1.0%		± 1.0%		± 1.0%		± 1.0%		± 1.0%		
	SETUP, RISE TIME	500ms, 50ms/230VAC 500ms, 50ms/115VAC at full load										
	HOLD UP TIME (Typ.)	30ms/230VAC 12ms/115VAC at full load										
INPUT	VOLTAGE RANGE	85 ~ 264VAC (277VAC operational) 120 ~ 370VDC (390VDC operational)										
	FREQUENCY RANGE	47 ~ 63Hz										
	EFFICIENCY (Typ.)	85%		88%		89%		90%		91%		
	AC CURRENT (Typ.)	1.2A/115VAC 0.8A/230VAC										
	INRUSH CURRENT (Typ.)	COLD START 30A/115VAC 60A/230VAC										
PROTECTION	OVERLOAD	105 ~ 160% rated output power Hiccup mode when output voltage <50%, recovers automatically after fault condition is removed Constant current limiting within 50% ~100% rated output voltage, recovers automatically after fault condition is removed										
	OVER VOLTAGE	5.75 ~ 6.75V		14.2 ~ 16.2V		18.8 ~ 22.5V		30 ~ 36V		56.5 ~ 64.8V		
		Protection type : Shut down o/p voltage, re-power on to recover										
ENVIRONMENT	WORKING TEMP.	-30 ~ +70°C (Refer to "Derating Curve")										
	WORKING HUMIDITY	20 ~ 90% RH non-condensing										
	STORAGE TEMP., HUMIDITY	-40 ~ +85°C, 10 ~ 95% RH non-condensing										
	TEMP. COEFFICIENT	± 0.03%/°C (0 ~ 50°C) RH non-condensing										
	VIBRATION	10 ~ 500Hz, 2G 10min./1cycle, period for 60min. each along X, Y, Z axes; Mounting: Compliance to IEC60068-2-6										
	OPERATING ALTITUDE	2000 meters										
	OVER VOLTAGE CATEGORY	III ; According to EN61558, EN50178, EN60664-1, EN62477-1 ; altitude up to 2000 meters										
SAFETY & EMC (Note 4)	SAFETY STANDARDS	UL60950-1, UL508, TUV EN61558-2-16, IEC60950-1, EAC TP TC 004, BSMI CNS14336-1 approved; Design refer to TUV EN60950-1										
	WITHSTAND VOLTAGE	I/P-O/P:4KVAC										
	ISOLATION RESISTANCE	I/P-O/P:100M Ohms / 500VDC / 25°C / 70% RH										
	EMC EMISSION	Parameter	Standard				Test Level / Note					
		Conducted	EN55032(CISPR32), CNS13438				Class B					
		Radiated	EN55032(CISPR32), CNS13438				Class B					
		Harmonic Current	EN61000-3-2				Class A					
		Voltage Flicker	EN61000-3-3				-----					
	EMC IMMUNITY		EN55024, EN55035, EN61000-6-2, EN61204-3									
		Parameter	Standard				Test Level /Note					
		ESD	EN61000-4-2				Level 3, 8KV air; Level 2, 4KV contact, criteria A					
		Radiated Susceptibility	EN61000-4-3				Level 3, criteria A					
		EFT/Burest	EN61000-4-4				Level 3, criteria A					
		Surge	EN61000-4-5				Level 4, 2KV/L-N, criteria A					
		Conducted	EN61000-4-6				Level 3, criteria A					
		Magnetic Field	EN61000-4-8				Level 4, criteria A					
		Voltage Dips and interruptions	EN61000-4-11				> 95% dip 0. 5 periods, 30% dip 25 periods, > 95% interruptions 250 periods					
OTHERS	MTBF	927.6K hrs min. MIL-HDBK-217F (25°C)										
	DIMENSION	52.5*90*54.5mm (W*H*D)										
	PACKING	190g/60pcs/12.4Kg/0.97CUFT										
NOTE	1. All parameters NOT specially mentioned are measured at 230VAC input, rated load and 25°C of ambient temperature. 2. Ripple & noise are measured at 20MHz of bandwidth by using a 12" twisted pair-wire terminated with a 0.1µf & 47µf parallel capacitor. 3. Tolerance : includes set up tolerance, line regulation and load regulation. 4. The power supply is considered as an independent unit, but the final equipment still need to re-confirm that the whole system complies with the EMC directives. For guidance on how to perform these EMC tests, please refer to “EMI testing of component power supplies.” (as available on http://www.meanwell.com) 5. The ambient temperature derating of 3.5°C/1000m with fanless models and of 5°C/1000m with fan models for operating altitude higher than 2000m(6500ft).											


■ Block Diagram



■ Derating Curve





■ Output Derating VS Input Voltage



Mechanical Specification

(Unit: mm , tolerance $\pm 0.5\text{mm}$)



ADMISSIBLE DIN-RAIL: TS35/7.5 OR TS35/15

Terminal Pin No. Assignment

Pin No.	Assignment	Pin No.	Assignment
1,2	-V	5	AC/L
3,4	+V	6	AC/N

Installation Manual

Please refer to : <http://www.meanwell.com/manual.html>