

Model		PSE-800	PSE-1200	PSE-2000
Capacity		800VA/400W	1200VA/600W	2000VA/1000W
AC Input	Normal Voltage	220/230/240VAC		
	Input Voltage Range	161VAC ~ 288VAC (-30%,+25%)		
	Phase	1 Phase 2 Wires		
	Frequency	50Hz or 60Hz		
AC Output	Output Voltage Range	207VAC ~ 253VAC (+/-10%)		
	Frequency	50Hz or 60Hz		
DC Output	Output Voltage Range	5VDC (+/-2%)		
Outlets	AVR/Surge only	3/3		
Protection	Network Surge Suppression	RJ-45/RJ-11		
	Overload	Manual Reset Circuit Switch		
	Short Circuit	Manual Reset Circuit Switch		
LED	Power On/Off	Green LED		
	Boost	Yellow LED		
	Buck	Yellow LED		
Environment	Operating Temperature	0 ~ 40°C		
	Relative Humidity	0 ~ 95%, non-condensing		
	Audible Noise	< 40dB at 1M		
Physical	Dimension(D*W*H)	280*120*80mm		
	Net Weight	1.4Kgs	1.7Kgs	2.3Kgs
Design,Manufacture,Services		ISO 9001-2000		
Warranty		1 year		