

HDR Din Rail Power Supply



Model	HDR-15	HDR-30	HDR-60	HDR-100	HDR-150
Output	5V2.4A	5V3A	5V6.5A	12V7.5A	12V11.3A
	12V1.25A	12V2.5A	12V5A	15V6.5A	15V9.5A
	15V1A	15V2A	15V4A	24V4.2A	24V6.25A
	24V0.63A	24V1.5A	24V2.5A	48V2.1A	48V3.2A
	48V0.32A	48V0.75A	48V1.25A		
Dimension (L×W×H) mm	17.5*90*54.5	35*90*54.5	52.5*90*54.5	70*90*54.5	105*90*54.5
Input Voltage Range	AC 85V~264V ;120~370VDC				
Over Voltage Protection	110%~140%				
Over Load Protection	>105%~170% Rated Output Power				
Working Temperature	-20~+70°C				
Product Service Life	3 Year Warranty				
Short Circuit Protection	Hiccup restart				
DC Adjustment Range	±15% Rated Output Voltage				
Withstand Voltage	I/P-O/P: 3K VAC I/P-FG: 1.5K VAC, 1 Minute				
Features	.Universal AC input/Full range		.DC output voltage adjustable		
	.No load power consumption<0.3W		.Compact size with 1SU~4SU width		
	.Cooling by free air convection		.Can be installed on DIN rail TS-35/7.5or 15		
	.protections:Short circuit/Overload/Over temperature				